

## technical data sheet

# BOSTIK 9252

## Metal Primer

### PRODUCT

**Bostik 9252** is a thin, yellow/brown brushable liquid mainly used on metal surfaces as a primer.

### DESCRIPTION

A yellow, brushable primer that is chiefly used as part of the Bostik 2402 adhesive system, but can also be used with other Bostik Neoprene Contact Adhesives, as well as Bostik Polyurethane and Nitriles. **Bostik 9252** promotes good adhesion to metallic surfaces and fibreglass and may be used to increase adhesion on smooth surfaces by giving a better 'key'.

### PERFORMANCE PROPERTIES

Resistant to	Oil and Water
Temperature Range	Satisfactory between -50°C and + 120°C
Aging	Very good
Coverage	Approx. 6-7 m <sup>2</sup> /L on one surface
Type	Synthetic Rubber/Resin Solution
Viscosity	Brookfield 800cps @ 20°C
Solids	31%
Flash Point	-7°C
Resistant to	Oil and Water

### PACKAGING

Supplied in 500ml containers and 20 Litre drums

### APPLICATION INSTRUCTIONS

- For optimum adhesion, it is essential that the surface is thoroughly degreased with Bostik 9907 Solvent and abraded if possible.
- Prior to use, stir the primer thoroughly (important).
- Apply an even, thin coat of primer by brush
- Allow to dry completely (minimum of 1 hour) before applying the appropriate adhesive.

*The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.*

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD**

### P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

### HEALTH AND SAFETY

The solvents are highly flammable. Keep away from heat and naked flame. Refer M.S.D.S. for specific details.

### CLEAN-UP

Use Bostik 9907

### STORAGE

Shelf Life 2 years from date of manufacture when stored in cool, dry place.

### BOSTIK 9252 PRIMER

ITEM NO.	STOCK SIZE
043958	500ml can
198994	20 Litre drum

### FOR FURTHER INFORMATION

**BOSTIK FINDLEY AUSTRALIA PTY LTD**  
 Phone: +61-3-9279 9333  
 Fax: +61-3-9279 9240

**BOSTIK FINDLEY NZ LIMITED**  
 Phone: +64-4-567 5119  
 Fax: +64-4-567-5412

**BOSTIK FINDLEY SINGAPORE PTE LTD**  
 Phone: +65-863 4088  
 Fax: +65-863 4077

**BOSTIK FINDLEY (MALAYSIA) SDN BHD**  
 Phone: +606 764 3246  
 Fax: +606 764 3248

**SYDNEY**  
 Phone: 02 8825 3488  
 Fax: 02 8825 3411

**ADELAIDE**  
 Phone: 08 8244 0511  
 Fax: 08 8244 0522

**PERTH**  
 Phone: 08 9331 7666  
 Fax: 08 9331 7677

**BRISBANE**  
 Phone: 07 3265 2377  
 Fax: 07 3265 5421

**(ABN 79 003 893 838)**



Product: Bostik 9252 Metal Primer  
 Issue Date: October 2001  
 Issue No: 1  
 Division: Industrial  
 Total Pages: 1