



swift[®] tak 2050

Application

swift[®] tak 2050 is a pressure sensitive, dispersion based adhesive used for coating materials like textiles, foams, foils and similar materials.

Properties

swift[®] tak 2050 exhibits high surface tack, good heat and plasticizer resistance.

Technical Data

Base:	Acrylic dispersion
Colour:	Beige
Viscosity (Brookfield):	Ca. 20.000 mPas
Density:	Ca. 1,01 g/cm ³
Thinner:	Water
Cleaner for dried on adhesive:	helmitin [®] 691
Application method:	Roll coater, coating knife or notched trowel
Coverage:	80 - 150 g/m ² , depending on material
Storage life:	Ca. 9 months
Conditions for storage and transport:	Well closed at temperatures between 5 °C and 25 °C
Sensitive to cold:	Yes
Inflammable:	No
Labelling acc. to regulations for dangerous goods:	None See Safety data sheet

* The viscosity indicated above is based on a temperature of 20 °C prevailing at the time of production. Minor deviations may occur during storage.

Instructions for use

swift[®] tak 2050 can be hand applied with a fine notched trowel. When coating larger areas, it should be applied with a roll coater or coating knife. After drying the coated materials should be covered with a qualified silicone foil or paper. Drying time varies depending on temperature, amount of adhesive applied and the material used. For some materials, such as textiles and foams, the adhesive should be applied to the silicone paper, allowed to dry and transfer onto the desired material.

Packaging

10 kg Pail, 140 kg Drum

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.



H.B. Fuller

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

H.B. Fuller Europe

info-europe@hbfuller.com

Contact us

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.