



Product Data

TECHNICLEAN AS 58

Issue Number 1
29/06/2007

Hydrocarbon Solvent Cleaner

DESCRIPTION

Castrol Techniclean AS 58 is a low odour solvent cleaner.
(Formerly known as Careclean L 60)

APPLICATION

Castrol Techniclean AS 58 is a low odour solvent cleaner. It has excellent solvency powers and is compatible with all metal substrates and most non metal substrates. It has been developed specifically as an alternative to chlorinated solvent cleaner.

● **Soak Tanks**

Components should be fully immersed in neat product; contact time depends on soil severity.

Ultrasonic Tanks

Components should be fully immersed in neat product.

Wipe Method

Product should be applied neat via hand held spray or brush, the surface is then wiped to a clean dry finish. This product is also available in aerosol cans.

FEATURES

- ◆ Non ozone depleting
- ◆ Low odour
- ◆ Virtually aromatic free
- ◆ Fast drying
- ◆ Excellent cleaning ability & residue free finish

BENEFITS

- ◆ Environmentally friendly
- ◆ Operator Acceptance
- ◆ Safer
- ◆ No long wait for next process
- ◆ Single stage wash

LIMITATIONS

- ◆ During application - May swell some rubber and plastics
- ◆ Should not be used for cleaning live electrical equipment



Product Data

TECHNICLEAN AS 58

TYPICAL PHYSICAL CHARACTERISTICS

Appearance	Water white mobile liquid
Relative Density @ 20°C, kg/l	0.76
Odour	Bland
Closed Flash Point, °C	56

APPROVALS

The components of Castrol Techniclean AS 58 are permitted by the US Food and Drug Administration for use in a variety of direct and indirect food applications.

Health and Safety information sheets are available for all Castrol products from the address below:

Castrol (U.K.) Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, England, Telephone:

Orders/Enquiries (08459)645111, Technical Enquiries (01793)452111, Fax (01793)486083

All reasonable care has been taken to ensure that the information contained in this publication is accurate as at the date of printing. It should be noted however that the information above may be affected by changes occurring subsequent to the date of printing in the blend formulation or methods of application of any of the products referred to or in the requirements of any specification approval relating to any such products.