



PTFE Tape TF-W27

self adhesive

acc. to DAN 269

and ABS 5766 A



Applications	sliding assistance and surface protection		
Material	Polytetrafluorethylene, specially coated, meets the requirements of DAN 269 and ABS 5766 A MBB Technical Specification no. TV 25/3519/73 issue 7		
Colour	grey		
Dimensions, width	from 5 mm up to 1200 mm		
Dimension, roll length	10 m		
Thickness	0.35 mm	0.65 mm	1.0 mm
Tensile force	30 N/25 mm	184 N/25 mm	283 N/25 mm
Elongation at break	35 %	33 %	20 %
Peel resistance on	30 N/25 mm	27 N/25 mm	28 N/25 mm
CRES			
Temperature range	-55 °C up to +85 °C		
Flammability	meets the requirements of FAR 25.853(a)(1)(ii)		



PTFE Tape TF-W29

self adhesive

acc. to ABS 5766 B



Applications:	sliding assistance and surface protection		
Material	Polytetrafluorethylene, specially coated, meets the requirements of ABS 5766B		
Colour	grey		
Dimensions, width ¹⁾	from 5 mm up to 300 mm		
Dimension, roll length ¹⁾	min. 2.5 m		
Thickness ¹⁾	0.15 mm	0.30 mm	0.55 mm
Tensile force	163 N/25 mm	213 N/25mm	351N/25mm
Elongation at break	582 %	417 %	> 680 %
Peel resistance on	12.5 N/25 mm	15.3 N/25mm	20 N/25 mm
CRES			
Temperature range	-55 °C up to +150 °C		
Flammability	meets the requirements of AITM 2.0002 B		
1) Other dimensions and thicknesses are available on request.			